

# **CS 247 – Scientific Visualization**

## **Lecture 22: Volume Visualization, Pt. 9; Vector / Flow Visualization, Pt. 1**

Markus Hadwiger, KAUST

# Reading Assignment #12 (until Apr 27)



Read (required):

- Data Visualization book
  - Chapter 6 (Vector Visualization)
    - Beginning (before 6.1)
    - Chapters 6.2, 6.3, 6.5
  - More general vector field basics (the book is not very precise on the basics)

[https://en.wikipedia.org/wiki/Vector\\_field](https://en.wikipedia.org/wiki/Vector_field)

Read (optional):

- Paper:  
Bruno Jobard and Wilfrid Lefer  
*Creating Evenly-Spaced Streamlines of Arbitrary Density,*

<http://citeseerx.ist.psu.edu/viewdoc/summary?doi=10.1.1.29.9498>

# Volume Rendering

# CUDA Kernel

- Image-based ray setup
  - Ray start image
  - Direction image
- Ray-cast loop
  - Sample volume
  - Accumulate color and opacity
- Terminate
- Store output

```
__global__
void RayCastCUDAKernel( float *d_output_buffer, float *d_startpos_buffer, float *d_direction_buffer )
{
    // output pixel coordinates
    dword screencoord_x = __umul24( blockIdx.x, blockDim.x ) + threadIdx.x;
    dword screencoord_y = __umul24( blockIdx.y, blockDim.y ) + threadIdx.y;

    // target pixel (RGBA-tuple) index
    dword screencoord_indx = ( __umul24( screencoord_y, cu_screensize.x ) + screencoord_x ) * 4;

    // get direction vector and ray start
    float4 dir_vec = d_direction_buffer[ screencoord_indx ];
    float4 startpos = d_startpos_buffer[ screencoord_indx ];

    // ray-casting loop
    float4 color = make_float4( 0.0f );
    float poscount = 0.0f;
    for ( int i = 0; i < 8192; i++ ) {

        // next sample position in volume space
        float3 samplepos = dir_vec * poscount + startpos;
        poscount += cu_sampling_distance;

        // fetch density
        float tex_density = tex3D( cu_volume_texture, samplepos.x, samplepos.y, samplepos.z );

        // apply transfer function
        float4 col_classified = tex1D( cu_transfer_function_texture, tex_density );

        // compute (1-previous.a)*tf.a
        float prev_alpha = -color.w * col_classified.w + col_classified.w;

        // composite color and alpha
        color.xyz = prev_alpha * col_classified.xyz + color.xyz;
        color.w += prev_alpha;

        // break if ray terminates (behind exit position or alpha threshold reached)
        if ( ( poscount > dir_vec.w ) || ( color.w > 0.98f ) ) {
            break;
        }
    }

    // store output color and opacity
    d_output_buffer[ screencoord_indx ] = __saturatef( color );
}
```

# Isosurface Ray-Casting

# Isosurface Ray-Casting



## Isosurfaces/Level Sets

- Scanned data (fit signed distance function to points, ...)
- Signed distance fields
- CSG (constructive solid geometry) operations




# Isosurface Ray-Casting




Opaque isosurfaces:  
only one sample contributes per ray/pixel

Discard all samples except first  
hit on isosurface / object boundary



Threshold transfer function / alpha test

**First hit ray casting**



# Intersection Refinement (1)





Fixed number of bisection / binary search steps

Virtually no impact on performance



Refine already detected  
intersection

Handle problems with small  
features / at silhouettes with  
adaptive sampling






# Intersection Refinement (2)

without refinement



with refinement




sampling distance 5 voxels (no adaptive sampling)

# Ray-Casting vs. Isosurface Ray-Casting



## Ray-Casting



Ray setup

Loop over ray

Sample scalar field

Classification

Shading

Compositing

## Isosurface Ray-Casting

Ray setup

Loop over ray

Sample scalar field

if value  $\geq$  isoValue (i.e., first hit)

break out of the loop

[Refine first hit location] (optional)

Shading

(Compositing not needed)

# Vector / Flow Visualization



# Online Demos and Info

Numerical ODE integration methods (Euler vs. Runge Kutta, etc.)

[https://demonstrations.wolfram.com/  
NumericalMethodsForDifferentialEquations/](https://demonstrations.wolfram.com/NumericalMethodsForDifferentialEquations/)

Flow visualization concepts


<https://www3.nd.edu/~cwang11/flowvis.html>

# Vector Fields: Motivation



### **Smoke angel**

A C-17 Globemaster III from the 14th Airlift Squadron, Charleston Air Force Base, S.C. flies off after releasing flares over the Atlantic Ocean near Charleston, S.C., during a training mission on Tuesday, May 16, 2006. The "smoke angel" is caused by the vortex from the engines.  
(U.S. Air Force photo/Tech. Sgt. Russell E. Cooley IV)




A wind tunnel model of a Cessna 182 showing a wingtip vortex.  
Tested in the RPI (Rensselaer Polytechnic Institute) Subsonic Wind Tunnel.

By Ben FrantzDale (2007).



[http://autospeed.com/cms/A\\_108677/article.html](http://autospeed.com/cms/A_108677/article.html)




[http://autospeed.com/cms/A\\_108677/article.html](http://autospeed.com/cms/A_108677/article.html)

**wool tufts**



smoke injection



[http://autospeed.com/cms/A\\_108677/article.html](http://autospeed.com/cms/A_108677/article.html)

smoke nozzles



[NASA, J. Exp. Biol.]



[http://autospeed.com/cms/A\\_108677/article.html](http://autospeed.com/cms/A_108677/article.html)

smoke nozzles

## Smoke injection

A. L. R. Thomas, G. K. Taylor, R. B. Srygley, R. L. Nudds, and R. J. Bomphrey. Dragonfly flight: free-flight and tethered flow visualizations reveal a diverse array of unsteady lift-generating mechanisms, controlled primarily via angle of attack. *J Exp Biol*, 207(24):4299–4323, 2004.








## Smoke injection

<http://www-me.ccny.cuny.edu/research/aerolab/facilities/images/wt2.jpg>




Clouds (satellite image)

*Juan Fernandez Islands*

# Clouds (satellite image)

<http://daac.gsfc.nasa.gov/gallery/frances/>



- **Vortex/ Vortex core lines**

- There is no exact definition of vortices
- capturing some swirling behavior




# Vector Fields



Each vector is usually thought of as a velocity vector


- Example for actual velocity: fluid flow
- But also force fields, etc. (e.g., electrostatic field)

**Eulerian** specification:



vectors given at grid points  
(grid points **do not** move)

**Lagrangian** specification:





vectors given at particle positions  
(particle positions **do** move)



# Vector Fields

Each vector is usually thought of as a velocity vector

- Example for actual velocity: fluid flow
- But also force fields, etc. (e.g., electrostatic field)




images from wikipedia

# Integral Curves / Stream Objects



Integrating velocity over time yields spatial motion







# Flow Field Example (1)

## Potential flow around a circular cylinder

[https://en.wikipedia.org/wiki/Potential\\_flow\\_around\\_a\\_circular\\_cylinder](https://en.wikipedia.org/wiki/Potential_flow_around_a_circular_cylinder)

Inviscid, incompressible flow that is irrotational (curl-free) and can be modeled as the gradient of a scalar function called the (scalar) velocity potential








# Flow Field Example (2)

Depending on Reynolds number, turbulence will develop

Example: von Kármán vortex street: vortex shedding

[https://en.wikipedia.org/wiki/Karman\\_vortex\\_street](https://en.wikipedia.org/wiki/Karman_vortex_street)



images from wikipedia

# Thank you.

## Thanks for material

- Helwig Hauser
- Eduard Gröller
- Daniel Weiskopf
- Torsten Möller
- Ronny Peikert
- Philipp Muigg
- Christof Rezk-Salama