

CS 380 - GPU and GPGPU Programming Lecture 25: GPU Virtual Geometry (and more Virtual Texturing)

Markus Hadwiger, KAUST

Reading Assignment #13 (until Dec 1)



Read (required):

- Look at Unreal Engine 5 virtual geometry system (Nanite)
 - https://dev.epicgames.com/documentation/en-us/unreal-engine/ nanite-virtualized-geometry-in-unreal-engine/
- Look at Unreal Engine 5 Nanite tech talk by Brian Karis (Journey to Nanite) slides
- Look at Unreal Engine 5 Lumen tech talk by Daniel Wright et al. slides
 - https://advances.realtimerendering.com/s2022/ SIGGRAPH2022-Advances-Lumen-Wright%20et%20al.pdf

Read (optional):

- Look at Unreal Engine 5 Nanite tech talk by Brian Karis (Journey to Nanite) talk
 - https://www.youtube.com/watch?v=NRnj_lnpORU

GPU Virtual Texturing

Virtual Texturing



Example #2:

Adaptive Shadow Maps (ASM)


On CPUs: Fernando et al., ACM SIGGRAPH 2001

Resolution-Matched Shadow Maps

• On GPUs: Aaron Lefohn et al., ACM Transactions on Graphics 2007


ASM Data Structure (Adaptive Shadow Maps)

Page table example



ASM Data Structure (Adaptive Shadow Maps)

- Adaptive Page Table
 - Map multiple virtual pages to single physical page



Aaron Lefohn
University of California, Davis

Virtual Texturing



Example #4:

Unreal Engine 5 Virtual Texturing

```
https://dev.epicgames.com/documentation/en-us/unreal-engine/
virtual-texturing-in-unreal-engine

https://dev.epicgames.com/documentation/en-us/unreal-engine/
streaming-virtual-texturing-in-unreal-engine

https://dev.epicgames.com/documentation/en-us/unreal-engine/
virtual-texture-memory-pools-in-unreal-engine

https://dev.epicgames.com/documentation/en-us/unreal-engine/
virtual-texturing-settings-and-properties-in-unreal-engine/
```

Unreal Engine 5 Virtual Texturing



Run-Time Virtual Texturing

Procedurally generate hires texture content; materials, etc.




Unreal Engine 5 Virtual Texturing



Streaming Virtual Texturing

- Stream texture data from disk; default tile size 128, up to 4K tiles
- Also: pre-baked hires light maps, etc.




Unreal Engine 5 Virtual Texture Memory Pools



One pool for virtual textures of each type/format

Can use residency mipmap bias (mipmap LOD bias)



Virtual Texturing



Example #5:


Petascale Volume Rendering

 Interactive Volume Exploration of Petascale Microscopy Data Streams Using a Visualization-Driven Virtual Memory Approach, Hadwiger et al., IEEE SciVis 2012

http://dx.doi.org/10.1109/TVCG.2012.240

Petascale Volume Rendering






multi-resolution page directory

Petascale Volume Rendering





Markus Hadwiger, KAUST

Virtual Geometry (and Texturing)


Unreal Engine 5 Virtual Geometry: Nanite



A Deep Dive into Nanite Virtualized Geometry (Siggraph 2021 course talk)

https://www.youtube.com/watch?v=eviSykqSUUw

Brian Karis, Epic Games



See also

- Keynote at HPG 2022: Journey to Nanite, Brian Karis https://www.youtube.com/watch?v=NRnj_lnpORU
- Lumen: Real-time Global Illumination in Unreal Engine 5 (Siggraph 2022 course talk),
 Daniel Wright et al., Epic Games
 https://advances.realtimerendering.com/s2022/SIGGRAPH2022-Advances-Lumen-Wright%20et%20al.pdf




The Dream

- Virtualize geometry like we did textures
- No more budgets
 - Polycount
 - Draw calls
 - Memory
- Directly use film quality source art
 - No manual optimization required
- No loss in quality












Pixel scale detail

- Can we hit pixel scale detail with triangles > 1 pixel?
 - Depends how smooth
 - In general no
- We need to draw pixel sized triangles








Tiny triangles

- Terrible for typical rasterizer
- Typical rasterizer:
 - Macro tile binning
 - Micro tile 4x4
 - Output 2x2 pixel quads
 - Highly parallel in pixels not triangles
- Modern GPUs setup 4 tris/clock max
 - Outputting SV_PrimitiveID makes it even worse
- Can we beat the HW rasterizer in SW?





Software Rasterization

3x faster!







Micropoly software rasterizer

- 128 triangle clusters => threadgroup size 128
- 1 thread per vertex
 - Transform position
 - Store in groupshared
 - If more than 128 verts loop (max 2)
- 1 thread per triangle
 - Fetch indexes
 - Fetch transformed positions
 - Calculate edge equations and depth gradient
 - Calculate screen bounding rect
 - For all pixels in rect
 - If inside all edges then write pixel

х	х	х	х
х	×	×	х
х	х	х	х
х	х	х	х







Hardware Rasterization

- What about big triangles?
 - Use HW rasterizer
- Choose SW or HW per cluster
- Also uses 64b atomic writes to UAV





Material shading

- Full screen quad per unique material
- Skip pixels not matching this material ID
- CPU unaware if some materials have no visible pixels
 - Material draw calls issued regardless
 - Unfortunate side effect of GPU driven
- How to do efficiently?
 - Don't test every pixel for matching material ID for every material pass








Material culling

- Material covers small portion of the screen
 - HiZ handles this OK
 - We can do better
- Coarse tile classification / culling
 - Render 8x4 grid of tiles per material
 - Same shading approach as full screen quads
- Tile killed in vertex shader from 32b mask
 - X=NaN








UV derivatives

- Still a coherent pixel shader so we have finite difference derivatives
- Pixel quads span
 - Triangles

⇔ Good!

- Also span
 - Depth discontinuities
 - UV seams
 - Different objects

Not good!









Analytic derivatives


- Compute analytic derivatives
 - Attribute gradient across triangle
- Propagate through material node graph using chain rule
- If derivative can't be evaluated analytically
 - Fall back to finite differences
- Used to sample textures with SampleGrad
- Additional cost tiny
 - <2% overhead for material pass
 - Only affects calculations that affect texture sampling
 - Virtual texturing code already does SampleGrad


















Virtual shadow maps

- Nanite enables new techniques
- 16k x 16k shadow maps everywhere
 - Spot: 1x projection
 - Point: 6x cube
 - Directional: Nx clipmaps
- Pick mip level where 1 texel = 1 pixel
- Only render the shadow map pixels that are visible
- Nanite culled and LODed to the detail required








Virtual shadow maps

- Page size = 128 x 128
- Page table = 128 x 128, with mips
- Mark needed pages
 - Screen pixels project to shadow space
 - Pick mip level where 1 texel = 1 pixel
 - Mark that page
- Allocate physical pages for all needed
- If cached page already exists use that
 - And wasn't invalidated
 - Remove from needed page mask








Lumen: Fully Dynamic Global Illumination



The Dream - dynamic indirect lighting

- Unlock new ways for players to interact with game worlds
- Instant results for lighting artists
 - o No more lighting builds
- Huge open worlds that couldn't have ever been baked
- Indoor quality comparable to baked lighting



MegaLights: Stochastic Direct (!) Lighting



